

M6.5

Z194.720









4,5 km/h 300 kg

6.000 kg



- For loads up to 6.000 kg.
- · Swivel wheel linked to the tiller.
- Pneumatic wheels.
- Optional electric lifting system.
- 5-levels speed adjustment.
- Wide range of accessories and connections.
















Zallys

Z194.720

M6.5

Unit: mm [inch]



Main sectors



AUTOMOTIVE



METALLURGICAL AND TURNING **INDUSTRY**



CARPENTRY AND PAINT SHOPS



GLASS INDUSTRY



PRODUCTION LINES




& RETAIL CHAINS



Performances on slopes

While the force expressed in N at the hook remains unchanged, the following circumstances may affect the towing capacity expressed in kg:

- type of ground on which the towing is performed;
- towing on flat ground or on a slope;
- use (or not) of ballasts;
- type of wheels mounted on the vehicle and on the trailer.





5 levels speed adjustment

On the new M6.5 tillerhead by Zallys a button for the adjustment of the speed of the machine is mounted as standard. By clicking it, at each click you switch to the next level. This allows a fast and easy selection of the correct speed based on the kind of maneuvre. The Flex-to-Go system has been studied to give a better maneuverability in confined spaces and more speed on the longer journeys.

Each click adds 20% more speed.

Speed ramp:

20% - 40% - 60% - 80% - 100%

Once the maximum speed is reached, by pressing the button again it returns to 20%.





Ergonomic driving

Zallys' tillerhead has been conceived and produced to make the use of the machine more ergonomic for the operator, guaranteeing the right comfort while driving during the work shift. Its ergonomic design allows to have all the driving controls at your fingertips, the display with the battery charge level and the power key for an easy and fast ignition. The structure is made of resistant materials in case of accidental bumps.







Pneumatic wheels

M6.5 is equipped with **pneumatic wheels**, suitable both for indoor and outdoor use, always guaranteeing the maximum grip and a really low level of vibrations. Moreover, the traction wheels are smaller compared to the other Zallys tow tugs' ones, to increase tow capacity and stability. The direction wheel is directly linked to the tiller, to move with incredible ease even the heaviest and bulkiest of loads.



Autonomy for a full workday

M6.5 is powered by two 105/130 Ah batteries, which guarantee the machine for 8 hours operation at continuous use. In case of a particularly intense use, it is possible to equip higher amperage batteries, or equip an interchangeable and extractable battery pack, for a 24 / 7 operation. In both cases they are easy and safe to recharge, thanks to the high frequency external battery pack.



Modular ballast system

Zallys modular system guarantees **maximum flexibility** on increasing the vehicle's performances. With just **10 kg unit weight,** single ballasts are lightweight and can be equipped **without physical effort by the operator**, while maintaining all their effectiveness.

STANDARD HITCH



















STANDARD HITCH

Electric lifting system (optional)



On request, it is possible to equip M6.5 with an electric lifting system kit, which allows the operator to easily and safely lift 2 wheeled trailers, directly from the controls on the tillerhead.





ACCESSORIES











Examples of applications

on various production sectors



METALLURGICAL INDUSTRY







INDUSTRIAL MAINTENANCE







PAINTING INDUSTRY









 $\bullet \circ \bullet$ the passion for moving

Zallys srl srl - Via Palazzina 1, Sarcedo 36030 (VI) - Italia

Contacts:

sales@zallys.com +39 0445 366785

Web site:

www.zallys.com



